


AS 201 ... AS 212 RILLENKUGELLAGER



	Abmessungen [mm]									Tragzahl [kN]		Gewicht
	d[mm]	D	Bi	Be	n	m	G	h	ds	dyn.C	stat.C0	[kg]
AS 201	12	40	22,0	12	6,0	16,0	4,5	3,6	M5 x 0,8	9,6	4,8	0,10
AS 202	15	40	22,0	12	6,0	16,0	4,5	3,6	M5 x 0,8	9,6	4,8	0,10
AS 203	17	40	22,0	12	6,0	16,0	4,5	3,6	M5 x 0,8	9,6	4,8	0,10
AS 204	20	47	25,0	14	7,0	18,0	4,5	3,9	M6 x 1,0	12,8	6,7	0,15
AS 205	25	52	27,0	15	7,5	19,5	5,5	3,9	M6 x 1,0	14,0	7,9	0,18
AS 206	30	62	30,0	16	8,0	22,0	5,5	5,0	M6 x 1,0	19,5	11,3	0,27
AS 207	35	72	32,0	17	8,5	23,5	6,5	5,5	M8 x 1,0	25,7	15,4	0,42
AS 208	40	80	34,0	18	9,0	25,0	7,0	6,0	M8 x 1,0	32,0	17,8	0,60
AS 209	45	85	41,2	19	9,5	31,7	8,2	6,3	M8 x 1,0	32,7	20,2	0,80
AS 210	50	90	41,6	20	10,0	31,6	9,2	6,5	M8 x 1,0	35,1	23,1	0,83
AS 211	55	100	45,3	23	11,8	33,5	9,8	7,2	M8 x 1,0	43,6	29,3	1,10
AS 212	60	110	53,7	24	14,9	38,8	9,8	8,0	M10 x 1,25	52,4	36,0	1,30