


BOLZEN Typ BS einsatzgehärtet (nicht genormt) BS ...



	DB h6	DN	LN H13	LNA	LB	LEM	AN	m	Sicherungsring g DIN 471
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]	
BS 12	12	11,5	1,10	33,00	35	30,0	1,0	0,030	12 x 1,00
BS 60	60	57,0	2,15	125,00	135	120,0	5,0	3,100	60 x 2,00
BS 30	30	28,6	1,60	74,00	79	70,0	2,5	0,440	30 x 1,50
BS 25	25	23,9	1,30	63,47	67	60,0	1,8	0,260	25 x 1,20
BS 16	16	15,2	1,10	43,00	46	40,0	1,5	0,075	16 x 1,00
BS 80	80	76,5	2,65	166,00	178	160,0	6,0	7,100	80 x 2,50
BS 20	20	19,2	1,30	53,40	57	50,0	1,8	0,140	20 x 1,20
BS 40	40	37,5	1,85	84,50	93	80,0	4,2	0,900	40 x 1,75
BS 100	100	96,5	3,15	207,00	221	200,0	7,0	14,400	100 x 3,00
BS 50	50	47,0	2,15	105,00	115	100,0	5,0	1,700	50 x 2,00