


Zylinderrollenlager

Kurz-Zeichen: NJ



Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NJ202-E	15	35	11	30.3	19.3	28,0	21,6	0,6	0,30	0,049
NJ203-E	17	40	12	35.1	22.1	32,5	24,7	0,6	0,30	0,070
NJ303-E	17	47	14	40.2	24.2	37,1	27,6	1,0	0,60	0,124
NJ2203-E	17	40	16	35.1	22.1	32,5	24,7	0,6	0,30	0,053
NJ204-E	20	47	14	41.5	26.5	38,8	29,7	1,0	0,60	0,117
NJ2304-E	20	52	21	45.5	27.5	42,4	31,3	1,1	0,60	0,219
NJ304-E	20	52	15	45.5	27.5	42,4	31,3	1,1	0,60	0,156
NJ2204-E	20	47	18	41.5	26.5	38,8	29,7	1,0	0,60	0,154
NJ2305-E	25	62	24	54.0	34.0	50,7	38,1	1,1	1,10	0,356
NJ2205-E	25	52	18	46.5	31.5	43,8	34,7	1,0	0,60	0,170
NJ205-E	25	52	15	46.5	31.5	43,8	34,7	1,0	0,60	0,140
NJ305-E	25	62	17	54.0	34.0	50,7	38,1	1,1	1,10	0,250
NJ406-M	30	90	23	73.0	45.0	68,4	50,3	1,5	1,50	0,859
NJ2206-E	30	62	20	55.5	37.5	52,5	41,3	1,0	0,60	0,261
NJ2306-E	30	72	27	62.5	40.5	59,2	45,0	1,1	1,10	0,540
NJ306-E	30	72	19	62.5	40.5	59,2	45,0	1,1	1,10	0,376
NJ206-E	30	62	16	55.5	37.5	52,5	41,1	1,0	0,60	0,213
NJ207-E	35	72	17	64.0	44.0	61,0	48,0	1,1	0,60	0,309
NJ407-M	35	100	25	83.0	53.0	78,2	58,8	1,5	1,50	1,160
NJ307-E	35	80	21	70.2	46.2	66,6	51,0	1,5	1,10	0,496
NJ2307-E	35	80	31	70.2	46.2	66,6	51,0	1,5	1,10	0,736
NJ2207-E	35	72	23	64.0	44.0	61,0	48,0	1,1	0,60	0,416
NJ308-E	40	90	23	80.0	52.0	75,9	57,6	1,5	1,50	0,674
NJ408-M	40	110	27	92.0	58.0	86,4	64,6	2,0	2,00	1,500
NJ2208-E	40	80	23	71.5	49.5	68,3	54,0	1,1	1,10	0,504
NJ208-E	40	80	18	71.5	49.5	68,3	54,0	1,1	1,10	0,389
NJ2308-E	40	90	33	80.0	52.0	75,9	0,0	1,5	1,50	0,978
NJ2309-E	45	100	36	88.5	58.5	84,1	64,4	1,5	1,50	1,330
NJ209-E	45	85	19	76.5	54.5	73,3	59,0	1,1	1,10	0,445
NJ409-M	45	120	29	100.5	64.5	94,6	71,6	2,0	2,00	1,840
NJ2209-E	45	85	23	76.5	54.5	73,3	59,0	1,1	1,10	0,544
NJ309-E	45	100	25	88.5	58.5	84,1	64,4	1,5	1,50	0,913
NJ2310-E	50	110	40	97.0	65.0	92,5	71,3	2,0	2,00	1,770
NJ2210-E	50	90	23	81.5	59.5	78,3	64,0	1,1	1,10	0,586

Zylinderrollenlager

Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NJ310-E	50	110	27	97.0	65.0	92,5	71,3	2,0	2,00	1,190
NJ210-E	50	90	20	81.5	59.5	78,3	64,0	1,1	1,10	0,503
NJ410-M	50	130	31	110.8	70.8	104,3	78,6	2,1	2,10	2,360
NJ311-E	55	120	29	106.5	70.5	101,4	77,5	2,0	2,00	1,510
NJ211-E	55	100	21	90.0	66.0	86,6	70,8	1,5	1,10	0,679
NJ411-M	55	140	33	117.2	77.2	110,7	0,0	2,1	2,10	2,880
NJ2211-E	55	100	25	90.0	66.0	86,6	70,8	1,5	1,10	0,812
NJ2311-E	55	120	43	106.5	70.5	101,4	77,5	2,0	2,00	2,270
NJ2312-E	60	130	46	115.0	77.0	109,6	84,4	2,1	2,10	2,830
NJ312-E	60	130	31	115.0	77.0	109,6	84,4	2,1	2,10	1,890
NJ412-M	60	150	35	127.0	83.0	119,5	91,6	2,1	2,10	3,420
NJ2212-E	60	110	28	100.0	72.0	96,1	77,6	1,5	1,50	1,100
NJ212-E	60	110	22	100.0	72.0	96,1	77,6	1,5	1,50	0,845
NJ2313-E	65	140	48	124.5	82.5	118,6	90,5	2,1	2,10	3,380
NJ2213-E	65	120	31	108.5	78.5	104,3	84,4	1,5	1,50	1,460
NJ413-M	65	160	37	135.3	89.3	127,7	98,3	2,1	2,10	4,150
NJ313-E	65	140	33	124.5	82.5	118,6	90,5	2,1	2,10	2,320
NJ213-E	65	120	23	108.5	78.5	104,3	84,4	1,5	1,50	1,060
NJ314-E	70	150	35	133.0	89.0	126,8	97,4	2,1	2,10	2,840
NJ2214-E	70	125	31	113.5	83.5	109,4	89,4	1,5	1,50	1,540
NJ214-E	70	125	24	113.5	83.5	109,4	89,4	1,5	1,50	1,180
NJ2314-E	70	150	51	133.0	89.0	126,8	97,4	2,1	2,10	4,100
NJ414-M	70	180	42	152.0	100.0	142,7	110,3	3,0	3,00	6,070
NJ2215-E	75	130	31	118.5	88.5	114,4	94,4	1,5	1,50	1,640
NJ2315-E	75	160	55	143.0	95.0	136,2	104,1	2,1	0,21	5,040
NJ415-M	75	190	45	160.5	104.5	150,7	115,8	3,0	3,00	7,210
NJ215-E	75	130	25	118.5	88.5	114,4	94,4	1,5	1,50	1,300
NJ315-E	75	160	37	143.0	95.0	136,2	104,1	2,1	0,21	3,390
NJ416-M	80	200	48	170.0	110.0	159,7	121,8	3,0	3,00	8,520
NJ216-E	80	140	26	127.3	95.3	122,9	101,5	2,0	2,00	1,580
NJ316-E	80	170	39	151.0	101.0	143,9	110,4	2,1	2,10	4,030
NJ2216-E	80	140	33	127.3	95.3	122,9	101,5	2,0	2,00	2,040
NJ2316-E	80	170	58	151.0	101.0	143,9	110,4	2,1	2,10	6,000
NJ317-E	85	180	41	160.0	108.0	152,7	117,8	3,0	3,00	4,710
NJ217-E	85	150	28	136.5	100.5	131,5	107,5	2,0	2,00	1,950
NJ2217-E	85	150	36	136.5	100.5	131,5	107,5	2,0	2,00	2,550
NJ417-M	85	210	52	177.0	113.0	165,7	125,8	4,0	4,00	10,000
NJ2317-E	85	180	60	160.0	108.0	152,7	117,8	3,0	3,00	6,850
NJ418-M	90	225	54	191.5	123.5	179,7	136,8	4,0	4,00	11,800
NJ2218-E	90	160	40	145.0	107.0	139,7	114,3	2,0	2,00	3,230
NJ218-E	90	160	30	145.0	107.0	139,7	114,3	2,0	2,00	2,410
NJ2318-E	90	190	64	169.5	113.5	161,6	124,0	3,0	3,00	8,190
NJ318-E	90	190	43	169.5	113.5	161,6	124,0	3,0	3,00	5,490

Zylinderrollenlager

Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NJ419-M	95	240	55	201.5	133.5	189,7	146,8	4,0	4,00	14,100
NJ319-E	95	200	45	177.5	121.5	169,6	132,0	3,0	3,00	6,440
NJ219-E	95	170	32	154.5	112.5	148,6	120,5	2,1	2,10	2,940
NJ2319-E	95	200	67	177.5	121.5	169,6	132,0	3,0	3,00	9,580
NJ2219-E	95	170	43	154.5	112.5	148,6	120,5	2,1	2,10	3,980
NJ220-E	100	180	34	163.0	119.0	156,9	127,3	2,1	2,10	3,550
NJ320-E	100	215	47	191.5	127.5	182,0	139,4	3,0	3,00	7,820
NJ420-M	100	250	58	211.0	139.0	198,2	152,8	4,0	4,00	16,100
NJ2220-E	100	180	46	163.0	119.0	156,9	127,3	2,1	2,10	4,850
NJ2320-E	100	215	73	191.5	127.5	182,0	139,4	3,0	3,00	12,300
NJ421-M	105	260	60	220.5	144.5	207,4	158,8	4,0	4,00	18,000
NJ221-E	105	190	36	171.5	125.5	165,1	134,5	2,1	2,10	4,170
NJ222-E	110	200	38	180.5	132.5	173,8	141,6	2,1	2,10	4,930
NJ422-M	110	280	65	235.0	155.0	220,9	170,3	4,0	4,00	22,800
NJ2222-E	110	200	53	180.5	132.5	173,8	141,6	2,1	2,10	6,890
NJ2322-E	110	240	80	211.0	143.0	200,9	155,6	3,0	3,00	16,900
NJ322-E	110	240	50	211.0	143.0	200,9	155,6	3,0	3,00	10,300
NJ324-E	120	260	55	230.0	154.0	218,7	168,1	3,0	3,00	13,500
NJ2324-E-M	120	260	86	230.0	154.0	218,7	168,1	3,0	3,00	23,500
NJ2224-E	120	215	58	195.5	143.5	187,8	153,2	2,1	2,10	8,540
NJ224-E	120	215	40	195.5	143.5	187,8	153,2	2,1	2,10	5,910
NJ2226-E	130	230	64	209.5	153.5	201,2	164,0	3,0	3,00	10,600
NJ326-E	130	280	58	247.0	167.0	235,2	181,7	4,0	4,00	16,500
NJ2326-E-M	130	280	93	247.0	167.0	235,2	181,7	4,0	4,00	29,200
NJ424-M	130	310	72	260.0	170.0	243,9	187,3	5,0	5,00	31,300
NJ226-E	130	230	40	209.5	153.5	201,2	164,0	3,0	3,00	6,630
NJ2228-E-M	140	250	68	225.0	169.0	216,7	179,4	3,0	3,00	14,700
NJ328-E	140	300	62	264.0	180.0	251,7	195,4	4,0	4,00	20,500
NJ228-E-M	140	250	42	225.0	169.0	216,7	179,4	3,0	3,00	9,460
NJ2328-E-M	140	300	102	264.0	180.0	251,7	195,4	4,0	4,00	36,600
NJ2330-E-M	150	320	108	283.0	193.0	269,8	209,5	4,0	4,00	43,800
NJ2230-E-M	150	270	73	242.0	182.0	233,2	193,1	3,0	3,00	18,700
NJ330-E	150	320	65	283.0	193.0	269,8	209,5	4,0	4,00	27,200
NJ230-E-M	150	270	45	242.0	182.0	233,2	193,1	3,0	3,00	11,900
NJ332-E	160	340	68	300.0	204.0	286,0	221,6	4,0	4,00	32,300
NJ2332-E-M	160	340	114	300.0	204.0	286,0	221,6	4,0	4,00	52,300
NJ2232-E-M	160	290	80	261.0	193.0	251,1	205,5	3,0	3,00	23,900
NJ232-E-M	160	290	48	259.0	195.0	249,6	206,8	3,0	3,00	14,800
NJ334-E	170	360	72	318.0	218.0	301,6	237,0	4,0	4,00	38,600
NJ234-E-M	170	310	52	279.0	207.0	268,5	218,4	4,0	4,00	18,400
NJ2334-E-M	170	360	120	320.0	216.0	303,0	237,0	4,0	4,00	62,300
NJ2234-E-M	170	310	86	281.0	205.0	269,9	219,0	4,0	4,00	29,800
NJ236-E-M	180	320	52	289.0	217.0	278,6	230,2	4,0	4,00	19,200

Zylinderrollenlager

Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NJ2336-E-M	180	380	126	339.0	227.0	320,8	248,0	4,0	4,00	72,900
NJ2236-E-M	180	320	86	291.0	215.0	280,0	229,0	4,0	4,00	30,900
NJ336-E	180	380	75	335.0	231.0	319,8	250,5	4,0	4,00	44,600
NJ2338-E-M	190	400	132	360.0	240.0	340,5	262,5	5,0	5,00	84,400
NJ2238-E-M	190	340	92	308.0	228.0	296,4	242,7	4,0	4,00	37,700
NJ238-E-M	190	340	55	306.0	230.0	295,0	244,0	4,0	4,00	23,200
NJ2340-E-M	200	420	138	377.0	253.0	356,9	276,1	5,0	5,00	97,200
NJ240-E-M	200	360	58	323.0	243.0	311,5	257,6	4,0	4,00	27,500
NJ340-E-M	200	420	80	370.0	258.0	351,8	279,0	5,0	5,00	58,100
NJ2240-E-M	200	360	98	325.0	241.0	312,9	256,3	4,0	4,00	45,300
NJ244-E-M	220	400	65	358.0	268.0	344,9	285,2	4,0	4,00	38,700
NJ248-E-M	240	440	72	393.0	293.0	376,6	312,0	4,0	4,00	52,500
NJ348-E-M	240	500	95	442.0	306.0	421,2	331,3	5,0	5,00	97,000
NJ252-E-M	260	480	80	429.0	317.0	410,8	336,9	5,0	5,00	69,400
NJ356-E-M	280	580	108	512.0	362.0	488,0	389,8	6,0	6,00	149,000