


Zylinderrollenlager

Kurz-Zeichen: N



Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
N202-E	15	35	11	30.3	19.3	0,0	21,6	0,6	0,30	0,047
N203-E	17	40	12	35.1	22.1	0,0	24,7	0,6	0,30	0,068
N204-E	20	47	14	41.5	26.5	0,0	29,7	1,0	0,60	0,112
N205-E	25	52	15	46.5	31.5	0,0	34,7	1,0	0,60	0,135
N206-E	30	62	16	55.5	37.5	0,0	41,1	1,0	0,60	0,205
N207-E	35	72	17	64.0	44.0	0,0	48,0	1,1	0,60	0,301
N208-E	40	80	18	71.5	49.5	0,0	54,0	1,1	1,10	0,358
N209-E	45	85	19	76.5	54.5	0,0	59,0	1,1	1,10	0,434
N210-E	50	90	20	81.5	59.5	0,0	64,0	1,1	1,10	0,488
N211-E	55	100	21	90.0	66.0	0,0	70,8	1,5	1,10	0,668
N212-E	60	110	22	100.0	72.0	0,0	77,6	1,5	1,50	0,827
N213-E	65	120	23	108.5	78.5	0,0	84,4	1,5	1,50	1,050
N214-E	70	125	24	113.5	83.5	0,0	89,4	1,5	1,50	1,160
N215-E	75	130	25	118.5	88.5	0,0	94,4	1,5	1,50	1,290
N216-E	80	140	26	127.3	95.3	0,0	101,5	2,0	2,00	1,550
N217-E	85	150	28	136.5	100.5	0,0	107,5	2,0	2,00	1,920
N218-E	90	160	30	145.0	107.0	0,0	114,3	2,0	2,00	2,370
N219-E	95	170	32	154.5	112.5	0,0	120,5	2,1	2,10	2,890
N220-E	100	180	34	163.0	119.0	0,0	127,3	2,1	2,10	3,500
N221-E-M	105	190	36	171.5	125.5	0,0	134,5	2,1	2,10	4,630
N222-E	110	200	38	180.5	132.5	0,0	141,6	2,1	2,10	4,850
N224-E	120	215	40	195.5	143.5	0,0	153,2	2,1	2,10	5,670
N226-E	130	230	40	209.5	153.5	0,0	164,0	3,0	3,00	6,510
N228-E-M	140	250	42	225.0	169.0	0,0	179,4	3,0	3,00	9,300
N230-E-M	150	270	45	242.0	182.0	0,0	193,1	3,0	3,00	11,700
N232-E-M	160	290	48	259.0	195.0	0,0	206,8	3,0	3,00	14,600
N234-E-M	170	310	52	279.0	207.0	0,0	218,4	4,0	4,00	18,000
N236-E-M	180	320	52	289.0	217.0	0,0	230,2	0,0	0,00	18,900
N238-E-M	190	340	55	306.0	230.0	0,0	244,0	4,0	4,00	22,800
N240-E-M	200	360	58	323.0	243.0	0,0	257,6	4,0	4,00	27,200
N244-E-M	220	400	65	358.0	268.0	344,9	0,0	4,0	4,00	38,500
N248-E-M	240	440	72	393.0	293.0	0,0	312,0	4,0	4,00	51,500