


Zylinderrollenlager

Kurz-Zeichen: NJ



Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NJ2203-E	17	40	16	35.1	22.1	32,5	24,7	0,6	0,30	0,053
NJ2304-E	20	52	21	45.5	27.5	42,4	31,3	1,1	0,60	0,219
NJ2204-E	20	47	18	41.5	26.5	38,8	29,7	1,0	0,60	0,154
NJ2305-E	25	62	24	54.0	34.0	50,7	38,1	1,1	1,10	0,356
NJ2205-E	25	52	18	46.5	31.5	43,8	34,7	1,0	0,60	0,170
NJ2206-E	30	62	20	55.5	37.5	52,5	41,3	1,0	0,60	0,261
NJ2306-E	30	72	27	62.5	40.5	59,2	45,0	1,1	1,10	0,540
NJ2207-E	35	72	23	64.0	44.0	61,0	48,0	1,1	0,60	0,416
NJ2307-E	35	80	31	70.2	46.2	66,6	51,0	1,5	1,10	0,736
NJ2208-E	40	80	23	71.5	49.5	68,3	54,0	1,1	1,10	0,504
NJ2308-E	40	90	33	80.0	52.0	75,9	0,0	1,5	1,50	0,978
NJ2209-E	45	85	23	76.5	54.5	73,3	59,0	1,1	1,10	0,544
NJ2309-E	45	100	36	88.5	58.5	84,1	64,4	1,5	1,50	1,330
NJ2310-E	50	110	40	97.0	65.0	92,5	71,3	2,0	2,00	1,770
NJ2210-E	50	90	23	81.5	59.5	78,3	64,0	1,1	1,10	0,586
NJ2211-E	55	100	25	90.0	66.0	86,6	70,8	1,5	1,10	0,812
NJ2311-E	55	120	43	106.5	70.5	101,4	77,5	2,0	2,00	2,270
NJ2312-E	60	130	46	115.0	77.0	109,6	84,4	2,1	2,10	2,830
NJ2212-E	60	110	28	100.0	72.0	96,1	77,6	1,5	1,50	1,100
NJ2213-E	65	120	31	108.5	78.5	104,3	84,4	1,5	1,50	1,460
NJ2313-E	65	140	48	124.5	82.5	118,6	90,5	2,1	2,10	3,380
NJ2314-E	70	150	51	133.0	89.0	126,8	97,4	2,1	2,10	4,100
NJ2214-E	70	125	31	113.5	83.5	109,4	89,4	1,5	1,50	1,540
NJ2315-E	75	160	55	143.0	95.0	136,2	104,1	2,1	0,21	5,040
NJ2215-E	75	130	31	118.5	88.5	114,4	94,4	1,5	1,50	1,640
NJ2316-E	80	170	58	151.0	101.0	143,9	110,4	2,1	2,10	6,000
NJ2216-E	80	140	33	127.3	95.3	122,9	101,5	2,0	2,00	2,040
NJ2317-E	85	180	60	160.0	108.0	152,7	117,8	3,0	3,00	6,850
NJ2217-E	85	150	36	136.5	100.5	131,5	107,5	2,0	2,00	2,550
NJ2318-E	90	190	64	169.5	113.5	161,6	124,0	3,0	3,00	8,190
NJ2218-E	90	160	40	145.0	107.0	139,7	114,3	2,0	2,00	3,230
NJ2319-E	95	200	67	177.5	121.5	169,6	132,0	3,0	3,00	9,580
NJ2219-E	95	170	43	154.5	112.5	148,6	120,5	2,1	2,10	3,980
NJ2320-E	100	215	73	191.5	127.5	182,0	139,4	3,0	3,00	12,300

Zylinderrollenlager

Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NJ2220-E	100	180	46	163.0	119.0	156,9	127,3	2,1	2,10	4,850
NJ2322-E	110	240	80	211.0	143.0	200,9	155,6	3,0	3,00	16,900
NJ2222-E	110	200	53	180.5	132.5	173,8	141,6	2,1	2,10	6,890
NJ2324-E-M	120	260	86	230.0	154.0	218,7	168,1	3,0	3,00	23,500
NJ2224-E	120	215	58	195.5	143.5	187,8	153,2	2,1	2,10	8,540
NJ2226-E	130	230	64	209.5	153.5	201,2	164,0	3,0	3,00	10,600
NJ2326-E-M	130	280	93	247.0	167.0	235,2	181,7	4,0	4,00	29,200
NJ2228-E-M	140	250	68	225.0	169.0	216,7	179,4	3,0	3,00	14,700
NJ2328-E-M	140	300	102	264.0	180.0	251,7	195,4	4,0	4,00	36,600
NJ2230-E-M	150	270	73	242.0	182.0	233,2	193,1	3,0	3,00	18,700
NJ2330-E-M	150	320	108	283.0	193.0	269,8	209,5	4,0	4,00	43,800
NJ2232-E-M	160	290	80	261.0	193.0	251,1	205,5	3,0	3,00	23,900
NJ2332-E-M	160	340	114	300.0	204.0	286,0	221,6	4,0	4,00	52,300
NJ2234-E-M	170	310	86	281.0	205.0	269,9	219,0	4,0	4,00	29,800
NJ2334-E-M	170	360	120	320.0	216.0	303,0	242,3	4,0	4,00	62,300
NJ2236-E-M	180	320	86	291.0	215.0	280,0	229,0	4,0	4,00	30,900
NJ2336-E-M	180	380	126	339.0	227.0	320,8	248,0	4,0	4,00	72,900
NJ2338-E-M	190	400	132	360.0	240.0	340,5	262,5	5,0	5,00	84,400
NJ2238-E-M	190	340	92	308.0	228.0	296,4	242,7	4,0	4,00	37,700
NJ2340-E-M	200	420	138	377.0	253.0	356,9	276,1	5,0	5,00	97,200
NJ2240-E-M	200	360	98	325.0	241.0	312,9	256,3	4,0	4,00	45,300