


Zylinderrollenlager

Kurz-Zeichen: NU



Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NU2203-E	17	40	16	35.1	22.1	35,2	0,0	0,6	0,30	0,051
NU2304-E	20	52	21	45.5	27.5	42,4	0,0	1,1	0,60	0,215
NU2204-E	20	47	18	41.5	26.5	38,8	0,0	1,0	0,60	0,146
NU2305-E	25	62	24	54.0	34.0	50,7	0,0	1,1	1,10	0,349
NU2205-E	25	52	18	46.5	31.5	43,8	0,0	0,0	0,00	0,165
NU2306-E	30	72	27	62.5	40.5	59,2	0,0	1,1	1,10	0,529
NU2206-E	30	62	20	55.5	37.5	52,5	0,0	1,0	0,60	0,255
NU2207-E	35	72	23	64.0	44.0	61,0	0,0	1,1	0,60	0,406
NU2307-E	35	80	31	70.2	46.2	66,6	0,0	1,5	1,10	0,723
NU2208-E	40	80	23	71.5	49.5	68,3	0,0	1,1	1,10	0,492
NU2308-E	40	90	33	80.0	52.0	75,9	0,0	1,5	1,50	0,958
NU2309-E	45	100	36	88.5	58.5	84,1	0,0	1,5	1,50	1,300
NU2209-E	45	85	23	76.5	54.5	73,3	0,0	1,1	1,10	0,532
NU2310-E	50	110	40	97.0	65.0	92,5	0,0	2,0	2,00	1,750
NU2210-E	50	90	23	81.5	59.5	78,3	0,0	1,1	1,10	0,573
NU2211-E	55	100	25	90.0	66.0	86,6	0,0	1,5	1,10	0,796
NU2311-E	55	120	43	106.5	70.5	101,4	0,0	2,0	2,00	2,230
NU2312-E	60	130	46	115.0	77.0	109,6	0,0	2,1	2,10	2,780
NU2212-E	60	110	28	100.0	72.0	96,1	0,0	1,5	1,50	1,080
NU2313-E	65	140	48	124.5	82.5	118,6	0,0	2,1	2,10	3,320
NU2213-E	65	120	31	108.5	78.5	104,3	0,0	1,5	1,50	1,430
NU2314-E	70	150	51	133.0	89.0	126,8	0,0	2,1	2,10	4,020
NU2214-E	70	125	31	113.5	83.5	109,4	0,0	1,5	1,50	1,520
NU2215-E	75	130	31	118.5	88.5	114,4	0,0	1,5	1,50	1,600
NU2315-E	75	160	55	143.0	95.0	136,2	0,0	2,1	0,21	4,950
NU2216-E	80	140	33	127.3	95.3	122,9	0,0	2,0	2,00	2,010
NU2316-E	80	170	58	151.0	101.0	143,9	0,0	2,1	2,10	5,890
NU2217-E	85	150	36	136.5	100.5	131,5	0,0	2,0	2,00	2,500
NU2317-E	85	180	60	160.0	108.0	152,7	0,0	3,0	3,00	6,720
NU2318-E	90	190	64	169.5	113.5	161,6	0,0	3,0	3,00	8,040
NU2218-E	90	160	40	145.0	107.0	139,7	0,0	2,0	2,00	3,170
NU2219-E	95	170	43	154.5	112.5	148,6	0,0	2,1	2,10	3,900
NU2319-E	95	200	67	177.5	121.5	169,6	0,0	3,0	3,00	9,400
NU2320-E	100	215	73	191.5	127.5	182,0	0,0	3,0	3,00	12,100

Zylinderrollenlager

Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NU2220-E	100	180	46	163.0	119.0	156,9	0,0	2,1	2,10	4,770
NU2322-E	110	240	80	211.0	143.0	200,9	0,0	3,0	3,00	16,600
NU2222-E	110	200	53	180.5	132.5	173,8	0,0	2,1	2,10	6,760
NU2324-E-M	120	260	86	230.0	154.0	218,7	0,0	3,0	3,00	23,200
NU2224-E	120	215	58	195.5	143.5	187,8	0,0	2,1	2,10	8,380
NU2326-E-M	130	280	93	247.0	167.0	235,2	0,0	4,0	4,00	28,800
NU2226-E	130	230	64	209.5	153.5	201,2	0,0	3,0	3,00	10,400
NU2328-E-M	140	300	102	264.0	180.0	251,7	0,0	4,0	4,00	36,000
NU2228-E-M	140	250	68	225.0	169.0	216,7	0,0	3,0	3,00	14,500
NU2230-E-M	150	270	73	242.0	182.0	233,2	0,0	3,0	3,00	18,400
NU2330-E-M	150	320	108	283.0	193.0	269,8	0,0	4,0	4,00	43,200
NU2332-E-M	160	340	114	300.0	204.0	286,0	0,0	4,0	4,00	51,500
NU2232-E-M	160	290	80	261.0	193.0	251,1	0,0	3,0	3,00	23,500
NU2334-E-M	170	360	120	320.0	216.0	303,0	0,0	4,0	4,00	61,400
NU2234-E-M	170	310	86	281.0	205.0	269,9	0,0	4,0	4,00	29,400
NU2336-EX-M	180	380	126	339.0	227.0	320,8	0,0	4,0	4,00	71,800
NU2236-E-M	180	320	86	291.0	215.0	280,0	0,0	4,0	4,00	30,500
NU2238-E-M	190	340	92	308.0	228.0	296,4	0,0	4,0	4,00	37,100
NU2338-E-M	190	400	132	360.0	240.0	340,5	0,0	5,0	5,00	83,100
NU2340-E-M	200	420	138	377.0	253.0	356,9	0,0	5,0	5,00	95,600
NU2240-E-M	200	360	98	325.0	241.0	312,9	0,0	4,0	4,00	44,700
NU2244-E-M	220	400	108	367.0	259.0	349,4	0,0	4,0	4,00	61,600
NU2344-E-M	220	460	145	413.0	277.0	391,2	0,0	5,0	5,00	121,000
NU2248-E-M	240	440	120	399.0	287.0	380,7	0,0	4,0	4,00	82,800
NU2348-E-M	240	500	155	447.0	303.0	424,0	0,0	5,0	5,00	151,000
NU2352-E-M	260	540	165	484.0	324.0	458,4	0,0	6,0	6,00	189,000
NU2252-E-M	260	480	130	433.0	313.0	413,6	0,0	5,0	5,00	109,000
NU2356-E-M	280	580	175	521.0	351.0	493,8	0,0	6,0	6,00	234,000
NU2256-E-M	280	500	130	453.0	333.0	436,0	0,0	5,0	5,00	114,000
NU2260-E-M	300	540	140	495.0	355.0	472,6	0,0	5,0	5,00	143,000
NU2264-E-M	320	580	150	530.0	380.0	506,0	0,0	5,0	5,00	180,000
NU2272-E-M	360	650	170	588.0	428.0	562,0	0,0	6,0	6,00	254,000
NU2276-E-M	380	680	175	615.0	451.0	588,8	0,0	6,0	6,00	288,000