


# Zylinderrollenlager

## Kurz-Zeichen: NJ



| Kurz-Zeichen | Abmessungen [mm] |     |     |       |       |       |       |        |         | Masse  |
|--------------|------------------|-----|-----|-------|-------|-------|-------|--------|---------|--------|
|              | d                | D   | B   | E     | F     | D1    | d1    | rs min | r1s min | [kg]   |
| NJ2304-E     | 20               | 52  | 21  | 45.5  | 27.5  | 42,4  | 31,3  | 1,1    | 0,60    | 0,219  |
| NJ2305-E     | 25               | 62  | 24  | 54.0  | 34.0  | 50,7  | 38,1  | 1,1    | 1,10    | 0,356  |
| NJ2306-E     | 30               | 72  | 27  | 62.5  | 40.5  | 59,2  | 45,0  | 1,1    | 1,10    | 0,540  |
| NJ2307-E     | 35               | 80  | 31  | 70.2  | 46.2  | 66,6  | 51,0  | 1,5    | 1,10    | 0,736  |
| NJ2308-E     | 40               | 90  | 33  | 80.0  | 52.0  | 75,9  | 0,0   | 1,5    | 1,50    | 0,978  |
| NJ2309-E     | 45               | 100 | 36  | 88.5  | 58.5  | 84,1  | 64,4  | 1,5    | 1,50    | 1,330  |
| NJ2310-E     | 50               | 110 | 40  | 97.0  | 65.0  | 92,5  | 71,3  | 2,0    | 2,00    | 1,770  |
| NJ2311-E     | 55               | 120 | 43  | 106.5 | 70.5  | 101,4 | 77,5  | 2,0    | 2,00    | 2,270  |
| NJ2312-E     | 60               | 130 | 46  | 115.0 | 77.0  | 109,6 | 84,4  | 2,1    | 2,10    | 2,830  |
| NJ2313-E     | 65               | 140 | 48  | 124.5 | 82.5  | 118,6 | 90,5  | 2,1    | 2,10    | 3,380  |
| NJ2314-E     | 70               | 150 | 51  | 133.0 | 89.0  | 126,8 | 97,4  | 2,1    | 2,10    | 4,100  |
| NJ2315-E     | 75               | 160 | 55  | 143.0 | 95.0  | 136,2 | 104,1 | 2,1    | 0,21    | 5,040  |
| NJ2316-E     | 80               | 170 | 58  | 151.0 | 101.0 | 143,9 | 110,4 | 2,1    | 2,10    | 6,000  |
| NJ2317-E     | 85               | 180 | 60  | 160.0 | 108.0 | 152,7 | 117,8 | 3,0    | 3,00    | 6,850  |
| NJ2318-E     | 90               | 190 | 64  | 169.5 | 113.5 | 161,6 | 124,0 | 3,0    | 3,00    | 8,190  |
| NJ2319-E     | 95               | 200 | 67  | 177.5 | 121.5 | 169,6 | 132,0 | 3,0    | 3,00    | 9,580  |
| NJ2320-E     | 100              | 215 | 73  | 191.5 | 127.5 | 182,0 | 139,4 | 3,0    | 3,00    | 12,300 |
| NJ2322-E     | 110              | 240 | 80  | 211.0 | 143.0 | 200,9 | 155,6 | 3,0    | 3,00    | 16,900 |
| NJ2324-E-M   | 120              | 260 | 86  | 230.0 | 154.0 | 218,7 | 168,1 | 3,0    | 3,00    | 23,500 |
| NJ2326-E-M   | 130              | 280 | 93  | 247.0 | 167.0 | 235,2 | 181,7 | 4,0    | 4,00    | 29,200 |
| NJ2328-E-M   | 140              | 300 | 102 | 264.0 | 180.0 | 251,7 | 195,4 | 4,0    | 4,00    | 36,600 |
| NJ2330-E-M   | 150              | 320 | 108 | 283.0 | 193.0 | 269,8 | 209,5 | 4,0    | 4,00    | 43,800 |
| NJ2332-E-M   | 160              | 340 | 114 | 300.0 | 204.0 | 286,0 | 221,6 | 4,0    | 4,00    | 52,300 |
| NJ2334-E-M   | 170              | 360 | 120 | 320.0 | 216.0 | 303,0 | 62,3  | 4,0    | 4,00    | 62,300 |
| NJ2336-E-M   | 180              | 380 | 126 | 339.0 | 227.0 | 320,8 | 248,0 | 4,0    | 4,00    | 72,900 |
| NJ2338-E-M   | 190              | 400 | 132 | 360.0 | 240.0 | 340,5 | 262,5 | 5,0    | 5,00    | 84,400 |
| NJ2340-E-M   | 200              | 420 | 138 | 377.0 | 253.0 | 356,9 | 276,1 | 5,0    | 5,00    | 97,200 |