


Zylinderrollenlager

Kurz-Zeichen: NU



Kurz-Zeichen	Abmessungen [mm]									Masse
	d	D	B	E	F	D1	d1	rs min	r1s min	[kg]
NU406-M	30	90	23	73.0	45.0	68,4	0,0	1,5	1,50	0,859
NU407-M	35	100	25	83.0	53.0	78,2	0,0	1,5	1,50	1,140
NU408-M	40	110	27	92.0	58.0	86,4	0,0	2,0	2,00	1,470
NU409-M	45	120	29	100.5	64.5	94,6	0,0	2,0	2,00	1,870
NU410-M	50	130	31	110.8	70.8	104,3	0,0	2,1	2,10	2,330
NU411-M	55	140	33	117.2	77.2	110,7	0,0	2,1	2,10	2,830
NU412-M	60	150	35	127.0	83.0	119,5	0,0	2,1	2,10	2,300
NU413-M	65	160	37	135.3	89.3	127,7	0,0	2,1	2,10	4,080
NU414-M	70	180	42	152.0	100.0	142,7	0,0	3,0	3,00	5,970
NU415-M	75	190	45	160.5	104.5	150,7	0,0	3,0	3,00	7,090
NU416-M	80	200	48	170.0	110.0	159,7	0,0	3,0	3,00	8,370
NU417-M	85	210	52	177.0	113.0	165,7	0,0	4,0	4,00	9,850
NU418-M	90	225	54	191.5	123.5	179,7	0,0	4,0	4,00	11,800
NU419-M	95	240	55	201.5	133.5	189,7	0,0	4,0	4,00	13,900
NU420-M	100	250	58	211.0	139.0	198,2	0,0	4,0	4,00	15,800
NU421-M	105	260	60	220.5	144.5	207,4	0,0	4,0	4,00	17,700
NU422-M	110	280	65	235.0	155.0	220,9	0,0	4,0	4,00	22,400
NU424-M	130	310	72	260.0	170.0	243,9	0,0	5,0	5,00	30,800